

CST Ladder Systems

Technical Data Sheet

CST

AQUASTORE®

TecTank™



CST offers a variety of ladder systems to fit customer's specific needs and provide total ladder climbing safety for workers on any site.


CST ladder systems offer a ladder with more than 60 years of safe climbing history. Installation of CST's ladder systems means instant compliance with OSHA's fixed ladder regulations.

Multiple OSHA compliant configurations to suit your needs

Made in the USA

Heavier aluminum ladder

Cage and platforms available in galvanized steel



Harness

Personal fall arrest system - rail and rung clamps



Shuttle

All CST + Ladder Systems are equipped with a personal fall arrest system.




FAQ's regarding OSHA changes

OSHA is phasing out the use of ladder cages as fall protection over the next 20 years as part of recent changes to 29 CFR 1910, Subpart D. The following list provides details on a few of the changes that are most applicable to fixed ladders:

- Fixed ladders that extend more than 24 ft. above a lower level and installed prior to 11/19/2018 must be equipped with a ladder safety system (i.e. personal fall arrest system and/or a cage).
- Each fixed ladder installed on and after 11/19/2018 is equipped with a ladder safety system (a cage is no longer considered as a ladder safety system).
- When a fixed ladder or cage, or any portion thereof, is replaced, a personal fall arrest system is installed in at least the section where the replacement is located.
- On and after 11/18/2036, all fixed ladders are to be equipped with a personal fall arrest system.
- When equipped with a personal fall arrest system, a fixed ladder must have rest platforms at maximum intervals of 150 ft.
- When equipped with a cage, fixed ladders must have offset landing platforms at maximum intervals of 50 ft.
- A cage can be used in combination with a personal fall arrest system provided the cage does not interfere with the operation of the system.

Additional information on the changes to the walking-working surfaces and personal fall protection systems regulations can be found at: www.osha.gov/walking-working-surfaces/faq



| CST Ladder Systems | Applicable Heights (ft) | | Compliance ⁽¹⁾ | | | | Included | | | | | |
|------------------------------|-------------------------|------------------|---------------------------|-----------|-----------------------|------------------------|------------------------|------------------------|------------------------|-------------|-----------------------------|-------------------|
| | < 24 | 24 - 150 | OSHA 1910 | AWWA D103 | ASCE 7-10 Sect. 4.5.4 | CCR Title 8-Sect. 3277 | Rest Platform < 150 ft | Rest Platform < 50 ft. | Rest Platform < 30 ft. | Safety Cage | Personal Fall Arrest System | Self-Closing Gate |
| Premium + | X | X | X | X | X | X | X | X | X | X | X | X |
| Premium⁽²⁾ | X | X ⁽³⁾ | X ⁽³⁾ | X | X | X | X | X | X | X | | X |
| Standard + | X | X | X | X | X | | X | X | | X | X | X |
| Economy + | X | X | X | X | X | | X | | | | X | X |
| Economy | X | | X | X | X | | | | | | | X |

Note:

1. Ladder compliance to any regulations not listed can be achieved but may require custom features
2. Premium ladder is comparable to CST legacy ladder. To expand existing Aquastore®, Harvestore® and TecStore™ ladders, the entire ladder section between existing step off platforms must be replaced
3. Only valid for ladders installed prior to 11/19/2018
4. For Harvestore agricultural applications not requiring OSHA compliance (as defined by OSHA), ladder and cage options are available

For more information call +1 844-44-TANKS or visit us online at www.cstindustries.com.

CST Industries, Inc. | 903 E 104th Street, Suite 900 | Kansas City, MO 64131 USA | Ph: 844-44-TANKS | www.cstindustries.com

©2018 CST Industries, Inc. Aquastore and Harvestore are registered trademarks and TecTank and TecStore are trademarks of CST Industries, Inc.



LS-DS-1802



TecTank™ **AQUASTORE®**

